

GENERAL SPECIFICATIONS

Displaying	: LCD
Max. displaying	: 1999 (3 ½) digits automatic polarity display
Measuring method	: Dual integral A/D conversion
Sampling rate	: Approx. 3 times/second
Over range display	: The highest digit displays "OL" or "-OL"
Low voltage display	: appears.
Working environment	: (0~40)°C, Relative humidity: <80% .
Power supply	: One 9V battery (6F22 or equivalent model).
Dimension	: 190 mm × 94.5 mm × 39.5 mm (length X width X height)
Weight	: About 450g (including 9V battery).

TECHNICAL SPECIFICATIONS

Accuracy: $\pm(a\% \times \text{reading data} + \text{digit})$, ensuring the accuracy. Environment temperature (23±5)°C, relative humidity <75% and the calibration warranty period lasts for one year from the date of leaving the factory.

DCV

Range	Resolution	Accuracy	Overload Protection
200mV	100uV	$\pm(0.5\%\text{rdg}+3\text{dgt})$	1000V DC / 750V AC RMS
2V	1mV		
20V	10mV		
200V	100mV		
1000V	1V		

Input impedance : All range is 10MΩ

Overload protection : 250V DV or AC effective value for range 200mV
1000V DC or 750V AC effective value for other range

ACV


Range	Resolution	Accuracy	Overload Protection
200mV	100uV	$\pm(0.8\%\text{rdg}+5\text{dgt})$	1000V DC / 750V AC RMS
2V	1mV		
20V	10mV		
200V	100mV		
750V	1V		

Input impedance : All range is 10MΩ

Overload protection : 250V DV or AC effective value for range 200mV
1000V DC or 750V AC effective value for other range

Frequency response : (40~400)Hz for all ranges

Displaying : Sine wave effective (AVG value response)



DCA

Range	Resolution	Accuracy	Overload Protection
2mA	1uA	$\pm(0.8\%\text{rdg}+10\text{dgt})$	200mA/250V
20mA	10uA		
200mA	100uA		
20A	1mA		

Max measurement voltage drop : 200mV.

Max input current : 20A (no more than 10 seconds).

Overload protection : the 200mA following measuring range is 0.2A/250V resettable fuse, the 20A measuring range 12A/250V fast-acting fuse.

ACA

Range	Resolution	Accuracy	Overload Protection
2mA	1uA	$\pm(1.0\%\text{rdg}+15\text{dgt})$	200mA/250V
20mA	10uA		
200mA	100uA		
20A	1mA		

Max measurement voltage drop : 200mV.

Max input current : 20A (no more than 10 seconds).

Overload protection : the 200mA following measuring range is 0.2A/250V resettable fuse, the 20A measuring range 12A/250V fast-acting fuse.

*Technical Specifications & Appearance are subject to change without prior notice

Resistance

Range	Resolution	Accuracy	Overload Protection
200Ω	0.1Ω	±(0.8%rdg+5dgt)	250V DC / AC effective value
2KΩ	1Ω		
20KΩ	10Ω		
200KΩ	100Ω	±(0.8%rdg+3dgt)	
2MΩ	1KΩ		
20MΩ	10KΩ	±(1.0%rdg+25dgt)	
2000MΩ	1MΩ	±[5.0%reading-10]+20]	

Open circuit voltage : Lower than 3V.

Overload protection : 250V DC and AC effective value.

Capacitance (C)

Range	Resolution	Accuracy	Overload Protection
20nF	10pF	±(2.5%rdg+20dgt)	36V DC / AC effective value
200nF	100pF		
2uF	1nF		
20uF	10nF		
200uF	100nF		

Testing frequency : 100Hz

Overload protection : 36V DC and AC effective value.

Inductance (C)

Range	Resolution	Accuracy	Overload Protection
2mH	1uH	±(2.5%rdg+30dgt)	36V DC / AC effective value
20mH	10uH		
200mH	100uH		
2H	1mH		
20H	10mH		

Testing frequency : 100Hz

Overload protection : 36V DC and AC effective value.

Temperature (°C)

Range	Resolution	Accuracy
(-20~1000)°C	1°C	± (1.0%rdg+4dgt) < 400°C ± (1.5%rdg+15dgt) ≥ 400°C

Thermo-element (banana plug type, temperature: -20~250°C)

Frequency (F)

Range	Resolution	Accuracy	Overload Protection
2kHz	1Hz	±(1.0%rdg+10dgt)	250V DC / AC effective value
20kHz	10Hz		
200kHz	100Hz		
2000kHz	1kHz		
10MHz	10kHz		

Input sensitivity : Higher than 2V effective value

Overload protection : 250V AC or DC effective value
(no more than 10 seconds)**Diode and continuity test**

Range	Resolution	Accuracy	Overload Protection
•	The positive DC current is approx 1mA, negative voltage is approx 3V	Positive voltage drop of diode	250V DC / AC effective value
	Open voltage is approx 3V	Buzzer sounds, the resistance is less than (30±10)W	

Overload protection : 250V AC or DC effective value

Warning : Don't input any voltage in this range

Temperature (°C)

Range	Displaying	Test Condition
hFE NPN or PNP	0~1000	Basic current is approx. 10uA, Vce is about 3V

*Technical Specifications & Appearance are subject to change without prior notice